

Tutorenprogramm - Strömungsmechanik II

Grundgleichungen - Musterlösung

1. Aufgabe

1. $\frac{\partial \rho \vec{v}}{\partial t}$: lokale Impulsänderung

$\nabla \cdot (\rho \vec{v} \vec{v})$: konvektive Impulsänderung

$-\nabla p$: Druckkraft

$\nabla \cdot \tau$: Reibungskraft

2. Vereinfachungen:

inkompressibel: $\Rightarrow \rho = \text{konst}$

2-dimensionales Problem: $\Rightarrow w = 0, \quad \frac{\partial}{\partial z} = 0,$

Konti: $\frac{d\rho}{dt} + \rho(\nabla \cdot \vec{v}) = 0 \quad \Rightarrow \quad \frac{\partial \rho}{\partial t} + u \frac{\partial \rho}{\partial x} + v \frac{\partial \rho}{\partial y} + \rho \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} \right) = 0$

inkompressibel: $\Rightarrow \quad \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0$

Impuls: inkompressibel: $\rho \frac{\partial \vec{v}}{\partial t} + \rho \nabla \cdot (\vec{v} \vec{v}) = -\nabla p + \eta \nabla^2 \vec{v}$

2D: $\rho \nabla \cdot (\vec{v} \vec{v}) = \rho \nabla \cdot \begin{pmatrix} u^2 & uv \\ uv & v^2 \end{pmatrix} = \rho \begin{pmatrix} \frac{\partial u^2}{\partial x} + \frac{\partial uv}{\partial y} \\ \frac{\partial uv}{\partial x} + \frac{\partial v^2}{\partial y} \end{pmatrix}$

$$= \rho \begin{pmatrix} \underbrace{u \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} \right)}_{\equiv 0, \text{Konti}} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} \\ \underbrace{v \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} \right)}_{\equiv 0, \text{Konti}} + u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} \end{pmatrix}$$

\Rightarrow x-Impuls: $\rho \frac{\partial u}{\partial t} + \rho \left(u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} \right) = -\frac{\partial p}{\partial x} + \eta \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right)$

\Rightarrow y-Impuls: $\rho \frac{\partial v}{\partial t} + \rho \left(u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} \right) = -\frac{\partial p}{\partial y} + \eta \left(\frac{\partial^2 v}{\partial x^2} + \frac{\partial^2 v}{\partial y^2} \right)$

3. Vereinfachungen:

eingeschwungen: $v = 0, p = p_a$

Konti: mit $v = 0 \quad \Rightarrow \quad \frac{\partial v}{\partial x} = \frac{\partial v}{\partial y} = \frac{\partial v}{\partial t} = 0$ folgt $\frac{\partial u}{\partial x} = 0$

Impuls: Mit $p = p_a \quad \Rightarrow \quad \frac{\partial p}{\partial x} = \frac{\partial p}{\partial y} = 0$

$$\text{Mit } \frac{\partial u}{\partial x} = 0 \quad \Rightarrow \quad \frac{\partial^2 u}{\partial x^2} = 0$$

$$\Rightarrow \quad x\text{-Impuls: } \rho \frac{\partial u}{\partial t} = \eta \frac{\partial^2 u}{\partial y^2}$$

$$\Rightarrow \quad y\text{-Impuls: } 0 = 0$$

Nur noch lokale Impulsänderung und Reibungsterm \rightarrow konvektive Terme sind verschwunden.

$$4. \quad \omega \uparrow \rightarrow \delta \downarrow \quad \eta \uparrow \rightarrow \delta \uparrow$$

Quelle: Frühjahr 2012

2. Aufgabe

1. Vereinfachungen:

$$\text{stationär: } \Rightarrow \frac{\partial}{\partial t} = 0, \quad \text{inkompressibel: } \Rightarrow \rho = \text{konst}$$

$$\text{2-dimensionales Problem: } \Rightarrow w = 0, \quad \frac{\partial}{\partial z} = 0, \quad \text{ausgebildet: } \Rightarrow \frac{\partial u}{\partial x} = 0, \quad \frac{\partial v}{\partial x} = 0$$

$$\text{Druck in } x\text{-Richtung konstant: } \Rightarrow \frac{\partial p}{\partial x} = 0$$

$$\text{Konti: } \frac{d\rho}{dt} + \rho(\nabla \cdot \vec{v}) = 0 \quad \Rightarrow \quad \frac{\partial \rho}{\partial t} + u \frac{\partial \rho}{\partial x} + v \frac{\partial \rho}{\partial y} + \rho \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} \right) = 0$$

$$\text{inkompressibel, stationär: } \Rightarrow \quad \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0$$

$$\text{Aus Konti folgt mit } \frac{\partial u}{\partial x} = 0 \quad \Rightarrow \quad \frac{\partial v}{\partial y} = 0 \quad \Rightarrow \quad v = \text{konst.} = 0, \text{ da } v(y=0) = 0$$

$$\text{x-Impuls: } \rho \frac{\partial u}{\partial t} + \rho \left(u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} \right) = -\frac{\partial p}{\partial x} + \frac{\partial \tau_{xx}}{\partial x} + \frac{\partial \tau_{xy}}{\partial y}$$

$$\text{y-Impuls: } \rho \frac{\partial v}{\partial t} + \rho \left(u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} \right) = -\frac{\partial p}{\partial y} + \frac{\partial \tau_{yx}}{\partial x} + \frac{\partial \tau_{yy}}{\partial y}$$

Mit oben genannten Vereinfachungen, Konti und $v = 0$:

$$\text{x-Impuls: } \Rightarrow \quad 0 = \frac{\partial \tau_{xx}}{\partial x} + \frac{\partial \tau_{xy}}{\partial y}$$

$$\text{y-Impuls: } \Rightarrow \quad 0 = -\frac{\partial p}{\partial y} + \frac{\partial \tau_{xy}}{\partial x} + \frac{\partial \tau_{yy}}{\partial y}$$

2. Geschwindigkeitsverteilung:

$$\text{Einsetzen von } \tau_{xx}, \tau_{xy}, \tau_{yy} \text{ ergibt } \Rightarrow \tau_{xx} = 0, \quad \tau_{yy} = 0, \quad \tau_{xy} = \eta \frac{\partial u}{\partial y}$$

$$\Rightarrow \text{mit } \frac{\partial u}{\partial x} = 0: \quad \text{x-Impuls: } 0 = \eta \frac{\partial^2 u}{\partial y^2}, \quad \text{y-Impuls: } 0 = \frac{\partial p}{\partial y}$$

$$\Rightarrow u(y) = \frac{c_1}{\eta} y + c_2$$

Randbedingung:

$$u(y=0) = 0 \quad \Rightarrow \quad c_2 = 0$$

$$u(y=h) = u_W \quad \Rightarrow \quad c_1 = \frac{u_W \eta}{h}$$

$$\Rightarrow u(y) = \frac{u_W}{h} y \quad \text{“Couette Strömung”}$$

Quelle: Herbst 2012